

STANDARD ALUMBRADO LED ROSCA NORMAL E-27

BOMBILLAS DE LED CON DIFUSOR MATE / OPAL

	Ref.	Lúmenes	Consumo W	Color	Rosca	Voltaje	Ø MM	Largo MM
	07SFN2	800 lm	8w = 60w	2700K	E27	230	60	102
	07SLMN3 <i>Alta Eficiencia</i> 	1521 lm	7,2w = 100w	3000K	E27	230	60	105
	85SMN2 <i>Dimable</i> 	1055 lm	7,5w = 75w	2700K	E27	230	60	105
	85SMN3 <i>Dimable</i> Radium	1055 lm	7,8w = 75w	3000K	E27	230	60	108
	85SMN4 <i>Dimable</i> 	1055 lm	7,5w = 75w	4000K	E27	230	60	108
	09STMDN2 <i>Dimable</i>	1055 lm	9w = 75w	2700K	E27	230	60	108
	10SKN3	930 lm	10w = 60w	3000K	E27	230	60	108
	10SKN4	950 lm	10w = 60w	4000K	E27	230	60	108
	10SKN6	932 lm	10w = 90w	6500K	E27	230	60	110
	11STMDN2 <i>Dimable</i>	1521 lm	11,2w = 100w	2700K	E27	230	70	108
	12SMN2 <i>Dimable</i> 	1521 lm	11w = 100w	2700K	E27	230	60	133
	10SKNCCT	950 lm	10w = 60w	3000K 4000K 6500K	E27	230	60	110
	15SKNCCT	1530 lm	15w	3000K 4000K 6500K	E27	230	60	115
	15SKN4	1500 lm	15w = 130w	4000K	E27	230	60	118
	17SLN5 <i>Dimable</i>	1700 lm	17w = 100w	5000K	E27	230	60	117

STANDARD ALUMBRADO LED ROSCA NORMAL E-27

BOMBILLAS DE LED CON DIFUSOR MATE / OPAL

	Ref.	Lúmenes	Consumo W	Color	Rosca	Voltaje	Ø MM	Largo MM
	18SKN3	1850 lm	18w = 150w	3000K	E27	230	80	159
	18SKN6	2350 lm	18w = 150w	6000K	E27	230	80	159
	18SMN2 <i>Dimable</i>	2452 lm	18w=150W	2700K	E27	230	70	128
	21SMN2 <i>Dimable</i> OSRAM	2452 lm	20w = 150w	2700K	E27	230	67	143
	24SMN2 OSRAM	3452 lm	24w = 200w	2700K	E27	230	95	162
	24SMN4 OSRAM	3452 lm	24w = 200w	4000K	E27	230	95	162

SOFTONE LED

	30SFN3	3350 lm	30w	3000K	E27	230	100	159
	40SFN3	3960 lm	45w	3000K	E27	230	247	140
	40SFN4	4500 lm	40w	4000K	E27	230	198	100
	50SFMN3	4500 lm	50w	3000K	E27	230	108	264
	50SFMN6	9000 lm	54w	6500K	E27	230	108	264

BITENSIÓN, DIFUSOR OPAL

	10S1N6	900 lm	10w = 64w	6500K	E27	100 - 240	60	110
	12S1N2	1050 lm	11w = 70w	2700K	E27	95 - 265	60	110

BOMBILLAS A BAJO VOLTAJE 12 AC/DC

	11S1N3	830 lm	9w = 60w	3000K	E27	12-14	60	112
	11S1N6	806 lm	9w = 60w	6000K	E27	12-24	60	112

Precios sujetos a cambios, según variaciones del mercado.

<https://monsoybenet.com/>

STANDARD ALUMBRADO LED ROSCA NORMAL E-27

BOMBILLAS DE LED, CON FILAMENTO VISTO

	Ref.	Lúmenes	Consumo W	Color	Rosca	Voltaje	Ø MM	Largo MM
	04SON2	470 lm	4w = 40w	2700K	E27	230	60	105
	07STCDN2 <i>Dimable</i>	806 lm	7w = 60w	2700K	E27	230	60	108
	07SON3	800 lm	8w	2700K	E27	230	60	105
	11SDN2 <i>Dimable</i>	1521 lm	11w	2700K	E27	230	70	126
	12SON2 <i>Dimable</i> OSRAM	1521 lm	11w = 100w	2700K	E27	230	60	105

TONO DE LUZ CÁLIDO, DIFUSOR COLOR CARAMELO

	04SFDAM <i>Dimable</i>	160 lm	4w	2000K	E27	230	60	105
	06SDAM <i>Dimable</i>	440 lm	5w = 40w	2200K	E27	230	60	105

BOMBILLAS A BAJO VOLTAJE 12-24 AC/DC

	06S2N2 <i>Dimable</i>	800 lm	6w = 60w	2700K	E27	12-24	60	110
---	---------------------------------	--------	-----------------	-------	-----	-------	----	-----

STANDARD ALUMBRADO LED ROSCA NORMAL E-27

	Ref.	Lúmenes	Consumo W	Color	Rosca	Voltaje	Difusor	Ø MM	Largo MM
BOMBILLA CASQUILLO BAYONETA									
	07SMB2 <i>Dimable</i> OSRAM	806 lm	6,5w=60w	2700K	B22	230	Opal	60	104
CON SENSOR DE MOVIMIENTO, RADAR									
	09SSRN3	830 lm	9w=60w	3000K	E27	230	Opal	60	105
CON SENSOR CREPUSCULAR DÍA/NOCHE + sensor PIR de presencia									
	10SSPN3	932 lm	10w=90w	3000K	E27	230	Opal	60	115
	10SSPN6	932 lm	10w=90w	6500K	E27	230	Opal	60	115
CON SENSOR CREPUSCULAR DÍA/NOCHE									
	12SSN3	1050 lm	11w	3000K	E27	230	Opal	65	124
	10SSN2 OSRAM	806 lm	8,8w=60w	2700K	E27	230	Opal	60	112
EFFECTOS RGB, CON MANDO A DISTANCIA (INCLUIDO)									
	05SLNR	700 lm	10w	RGB	E27	230	Opal	60	123
SMART WI-FI DIMABLE RGB									
	10SNSW	810 lm	10w	RGB	E27	230	Opal	60	117
	14SNSW OSRAM	1521 lm	14w=100w	RGB	E27	230	Opal	75	139
BOMBILLA STANDARD CON CÚPULA ESPEJADA									
	04SPON25 <i>Dimable</i>	250 lm	4w	2500K	E27	230	Cúpula dorada	60	105
	07SPN2 <i>Dimable</i>	595 lm	6w = 48w	2700K	E27	230	Cúpula cromada	60	105
	07SPON2 <i>Dimable</i>	660 lm	7w = 60w	2700K	E27	230	Cúpula dorada	60	105
	09SPN2 <i>Dimable</i>	1055 lm	9w = 75w	2700K	E27	230	Cúpula cromada	60	105